

ODYSSEY
BATTERY

Drop in replacement power built for land, sea and snow

When you need a powersports battery that is engineered to meet the rugged demands of motorcycle, All-Terrain Vehicle (ATV), Utility Terrain Vehicle (UTV) and watercraft applications, while providing a precise fit for "drop in" replacement, choose an ODYSSEY® battery.

Like all ODYSSEY® powersports batteries, three new units feature a non-spillable Absorbed Glass Mat (AGM) design that's built to take the pounding delivered by powersport vehicles – whether it's on land, sea or snow.

- Absorbed Glass Mat design with lead-calcium alloy grids, contributing to twice the overall power and three times the life of conventional batteries
- A sealed design, resulting in a maintenance-free battery
- The ability to resist extreme vibration, protecting against high impact shock vibrations that often lead to premature failure



ODS-AGM14



ODS-AGM20L



ODS-AGM30L

All values shown are nominal unless otherwise noted.

PART NUMBER	Voltage	PHCA** 5 sec [A]	CCA* [A]	Ah at 20-hr rate	Reserve Capacity [Minutes]	Maximum Length [in (mm)]	Maximum Width [in (mm)]	Maximum Total Height [in (mm)]	Nominal Weight [lb (kg)]	Terminal	Maximum Torque [in-lb (Nm)]
ODS-AGM14	12	575	240	16	24	5.9 (150)	3.5 (89)	5.7 (145)	11.9 (5.4)	M6 Receptacle	50 (5.6)
ODS-AGM20L	12	700	320	19	31	6.9 (177)	3.5 (89)	6.1 (156)	14.4 (6.5)	M6 Receptacle	50 (5.6)
ODS-AGM30L	12	850	450	32	50	6.7 (170)	5.2 (133)	6.9 (175)	22.9 (10.4)	M6 Receptacle	50 (5.6)

*Cold Start Performance S.A.E J537 Apr 2016

**Pulse Current

www.odysseybattery.com



Powered by **EnerSys**
Power/Full Solutions

ODYSSEY® Powersports Batteries

Rated Operating Temperature -40°F (-40°C) to 113°F (45°C) Metal Jacket¹ (MJ) option increases rated operating temperature to 176°F (80°C)

All values shown are nominal unless otherwise noted.

12 volt

PART NUMBER	PHCA** 5 sec [A]	CCA* [A]	Ah at 20-hr rate	Reserve Capacity [Minutes]	Maximum Length [in (mm)]	Maximum Width [in (mm)]	Maximum Total Height [in (mm)]	Maximum Container Height [in (mm)]	Weight [lb (kg)]	Terminal	Maximum Torque [in-lb (Nm)]
ODS-AGM8E	310	100	8	9	5.4 (138)	3.4 (86)	3.9 (99)	3.9 (99)	6 (2.5)	M4 Receptacle	8.9 (1.0)
ODS-AGM14	575	240	16	24	5.9 (150)	3.5 (89)	5.7 (145)	5.7 (145)	11.9 (5.4)	M6 Receptacle	50 (5.6)
ODS-AGM15L	460	150	13	18	6.9 (178)	3.3 (84)	4.9 (124)	5.1 (130)	11 (5.0)	M6 Receptacle	50 (5.6)
ODS-AGM16L ^{(1) (2) (3)}	520	170	16	24	7.2 (182)	3.0 (77)	6.4 (162)	6.6 (168)	15 (7.0)	M6 Receptacle	50 (5.6)
ODS-AGM16B	535	200	14	21	6.7 (170)	3.9 (99)	6.2 (159)	6.2 (157)	12 (5.5)	M6 Receptacle	40 (4.5)
ODS-AGM16CL	540	220	18	26	6.7 (170)	3.9 (99)	7.0 (177)	6.9 (175)	13 (6.0)	M6 Receptacle	40 (4.5)
ODS-AGM20L	700	320	19	31	6.9 (177)	3.5 (89)	6.1 (156)	6.1 (156)	14.4 (6.5)	M6 Receptacle	50 (5.6)
ODS-AGM28L ^{(1) (2) (3)}	900	330	28	48	6.6 (167)	6.9 (176)	4.7 (119)	5.0 (126)	24 (11.0)	M6 Receptacle	60 (6.8)
ODS-AGM28 ^{(1) (2) (3)}	900	330	28	48	6.6 (167)	6.9 (176)	4.7 (119)	5.0 (126)	24 (11.0)	M6 Receptacle	60 (6.8)
ODS-AGM30E	950	400	34	60	9.8 (250)	3.8 (97)	6.1 (156)	5.8 (146)	20 (9.0)	M6 Stud	35 (3.9)
ODS-AGM30L	850	450	32	50	6.7 (170)	5.2(133)	6.9 (175)	6.9 (175)	22.9 (10.4)	M6 Receptacle	50 (5.6)
ODS-AGM40E	1100	500	45	87	9.8 (250)	3.8 (97)	8.1 (206)	7.7 (196)	28 (13.0)	M6 Stud	35 (3.9)
ODS-AGM42L ^{(1) (2) (3)}	1200	540	42	78	7.8 (198)	6.5 (166)	6.4 (163)	6.7 (171)	38 (17.0)	M6 Receptacle	60 (6.8)
ODS-AGM42 ^{(1) (2) (3)}	1200	540	42	78	7.8 (198)	6.5 (166)	7.5 (192)	6.7 (171)	38 (17.0)	M6 Receptacle	N/A
ODS-AGM70 ^{(1) (2) (3)}	1550	810	68	142	13.0 (331)	6.6 (168)	6.6 (168)	6.9 (176)	61 (28.0)	M6 Receptacle	60 (6.8)
ODS-AGM70S ^{(1) (2)}	1550	810	68	142	13.0 (331)	6.6 (168)	7.4 (187)	6.9 (176)	61 (28.0)	5/16-18" Stud	60 (6.8)

*Cold Start Performance S.A.E J537 Apr 2016

**Pulse Current

¹ Metal jacket available, increases all nominal dimensions

² SAE terminal adapter available

³ Hold down kit available



EnerSys World Headquarters
2366 Bernville Road
Reading, PA 19605, USA
Tel: +1-800-964-2837

EnerSys EMEA
EH Europe GmbH
Baarerstrasse 18
6300 Zug, Switzerland

EnerSys APAC
No. 85, Tuas Avenue 1
Singapore 639518
Tel: +65 6558 7333

Want more info?
Scan code to access
the ODYSSEY® Battery
Literature Library

